



Features:

- Single pole relay board.
- Selectable 12V/24V DC operation.
- High quality screw connectors.
- LED indicator in series with relay coil for positive status identification.
- Screened printed circuit board.

NOT FOR MAINS USE

	Parameter	RLSP-V			Units
		Min	Typ	Max	
1	Operating voltage (breakout tab present)	10.0	12.0	17.0	VDC
2	Operating voltage (breakout tab removed)	17.0	24.0	28.0	VDC
3	Coil resistance		700		Ohm
4	Coil power		200		mw
5	Contact type		SPCO		
6	Contact rating (DC)	0.010	3.00		A @ 24VDC
7	Contact rating (AC)	0.010	3.00		A @ 120VAC
8	Operate time		8.0		ms
9	Release time		4.0		ms
10	Life expectancy (mechanical)		10 x 10 ⁶		operations
11	Life expectancy (electrical)		1 x 10 ⁵		operations
12	Operating temperature range	-25		+65	deg C
13	Dimensions		34x31x17h		mm
14	Mounting holes		3.0		mm

Operation

Apply 12VDC between POS and NEG terminals to operate the relay. The LED indicates the status of the relay (LED ON means relay energised). Note that to ensure the LED status accurately reflects the relay coil status, the LED is wired in series with the relay coil. This means that should the relay coil fail, the LED will not operate.

Relay terminals: NO=Normally Open, NC=Normally Closed and COM=Common.

COM Link

To simplify wiring in many common applications, the COM1 terminal of the relay may be connected to either the POS or NEG terminal using the link as shown.

12 Volt / 24 Volt Operation

As shipped, the RLSP-V operates as a 12V DC device. To make the board operate from 24V DC, remove the breakout tab as shown using a pair of pliers. Once removed, it cannot be replaced.

Security Wholesale 2001 Ltd
 CNR Sims & Great South Road Penrose, Auckland
 Postal: P.O Box 12-395 Penrose, Auckland.
 Ph: (09) 580 1147, Fax: (09) 580 1159.
 Web: www.swl.co.nz
 Email: trade@swl.co.nz

Warranty and Disclaimer

All information provided in this document is carefully prepared and offered in good faith as a guide for the installation, use and servicing of this product. We accept no responsibility for the incorrect installation or use of this product and reserve the right to change specifications and installation data at any time and without notice. Liability of TMD Consultants or any party involved in the design and/or manufacture of this product shall be limited to the replacement of faulty product returned to us within the warranty period (12 months) with proof of purchase. By using this product, you agree to these terms.